## IN THE CLAIMS

This listing of claims replaces all prior listings:

1. (Currently Amended) A positive electrode active material comprising coated particles, each coated particle having a layered structure with an inner particle having an outer surface covered at least in part by a coating layer, wherein:

said inner particle is a first compound oxide that includes LiNi<sub>0.70</sub>Mn<sub>0.30</sub>O<sub>2</sub> and LiNi<sub>0.70</sub>Co<sub>0.30</sub>O<sub>2</sub>, and said inner particle is capable of doping and undoping lithium;

said coating layer is adhered to said outer surface and said coating layer is a homogenous second compound oxide having a spinel structure in the cubic system of lithium and titanium selected from the group consisting of  $\text{Li}_4\text{Ti}_5\text{O}_{12}$ ,  $\text{Li}_2\text{TiO}_3$ ,  $\text{Li}_2\text{Ti}_3\text{O}_7$  and  $\text{Li}_4\text{Ti}_{4.90}\text{Mn}_{0.10}\text{O}_{12}$ ;

the ratio by weight of the first compound oxide to the second compound oxide is between 96:4 and 65:35, and

said coating layer effectively suppresses decomposition of electrolyte in contact therewith and maintains the conductivity of lithium ions in the positive electrode active material.

- 2. (Cancelled)
- 3. (Cancelled)
- 4. (Original) The positive electrode active material according to claim 1, wherein the positive electrode active material has a mean particle diameter of 5 to 20  $\mu$ m.
  - (Currently Amended) A non-aqueous electrolyte secondary battery comprising:
    a negative electrode active material; and

Response to September 1, 2010 Office Action Application No. 10/821,323 Page 3

a positive electrode active material, the positive active material comprising coated particles, each coated particle having a layered structure with an inner particle having an outer surface covered at least in part by a coating layer,

wherein,

said inner particle is a first compound oxide that includes LiNi<sub>0.70</sub>Mn<sub>0.30</sub>O<sub>2</sub> and LiNi<sub>0.70</sub>Co<sub>0.30</sub>O<sub>2</sub>, and said inner particle is capable of doping and undoping of lithium;

said coating layer is adhered to said outer surface <u>and said coating layer</u> is a second compound oxide of lithium and titanium having a spinel structure in the cubic system selected from the group consisting of Li<sub>4</sub>Ti<sub>5</sub>O<sub>12</sub>, Li<sub>2</sub>TiO<sub>3</sub>, Li<sub>2</sub>Ti<sub>3</sub>O<sub>7</sub> and Li<sub>4</sub>Ti<sub>4.90</sub>Mn<sub>0.10</sub>O<sub>12</sub>;

said inner particle compound and said coating layer compound are mixed in a 90:10 weight ratio, and

said coating layer effectively suppresses decomposition of electrolyte in contact with the active material and maintains conductivity of lithium ions in the active material.

6. (Previously Presented) A coated particle according to claim 1, wherein said coating layer and outer surface are fused by mechanofusion.

7. (Cancelled)